Exceptional service in the national interest



The Importability of Performance Tools: The Good, the Bad, and the Ugly of PMUs

Jeanine Cook
Scalable Architectures
SNL ABQ





Performance Tools



- Mostly talking about non-commercial tools
 - Tools that lots of us hack up to look at performance issues
 - MPI and node data
 - Interfaces like PAPI and mpip
 - Hoping not to have to learn intricacies of complicated performance tool
 - Tool doesn't quite do what we want it to

PMUs and Performance Counters (1)



- PMUs on CPUs are all different.
 - Implement different events
 - "Architected" PMUs provide subset of base events across model lines
 - Names of identical events can differ
 - Different number of physical counters
 - Divided amongst threads
 - Significant errata in PMU behavior
 - But info often not propagated to end user
- Event mapping tables
 - Connects event name and qualifiers to hardware register(s) configuration(s)
 - Some change frequently (Intel's https://download.01.org/perfmon/)
 - Some hardly get updated or are community supported (papi_presets)
 - Kernel contains some events with compile time mappings (perf list)
 - If hardware requires a change, no way to update map, either can't access event or may return strange results

PMUs and Performance Counters (2)



- Documentation is spotty at best, inaccurate at worst
 - Hard to really be sure of precisely what you're counting without investigation, sometimes microbenchmarking
 - EX: Events commonly counted at issue, so many overcount due to speculation and re-issue (e.g, SNB and IVB FP events)

PAPI Presets vs Native Events



- Presets offer portability... sort of
 - Event names consistent across platforms, but may map to different underlying native events, as best effort
 - Particular event may not actually count same behavior across systems
 - Particular event on single system may not count what event name reflects
 - SNB: PAPI_DP_OPS Counts DP FP add and multiply, but not divide instructions (separate counter for that)
 - » Use papi decode –a to see what presets count
 - » Decode libpfm events using showevtinfo from libpfm

Takeaways



- If using performance counters directly
 - Don't use presets, use natives
 - Be sure you know what you're counting
- Performance tools (commercial and home-grown) access PMUs
 - Restricts cross-platform usage

An attempt to make PMU/performance counter use easier and cross-platform...



Perfminer

Property of MinimalMetrics and SNL

Perfminer: Performance Analysis



- Performance Analysis
 - First line support tool for performance investigations
 - Low-overhead, scalable with simple instrumentation
 - "Inside-out" performance metrics from CPU, Memory, Network,
 Filesystem, Power, with localizing information
 - Data is per-thread and aggregated to all levels
 - Immediate, efficient, visual performance feedback via a web page
 - Drill down methodology with click through to investigate further
 - Supports using other tools
 - Enables continuous performance regression of system and applications
 - Actionable feedback (future development)
 - Suggestions for further testing; automatic generation of test scripts for Perfminer and potentially other tools

Perfminer: Performance Analysis



- Performance Analysis
 - Modular design
 - Collector, front-end, back-end
 - Java web-based, front-end
 - Python back end,
 - Schema-less NoSQL data store.
 - » Data is easily accessible for analytics via Excel, R, Matlab, Python, etc
 - Extensible analytics with Python
 - Elegant visualization using D3
 - No recompilation required
 - Easy to install (few dependencies) and trivial to use.
 - Full batch system integration (coming soon)

Perfminer: Performance as a Service National Laboratories

- Continuous monitoring infrastructure
 - Can opt in or out
- Deliver a report through email with actionable feedback

Job Info



now 10 c entries					Filter:		
Job ID 💠	Job Number 🍦	Owner	Nodes	Binary	Running Time	Finish Time	
BOJY380439	1025821	pjmucci	4	miniaero.exe	0:00:23	2016-03-20 10:05:25	
XIAT133711	1025820	pjmucci	1	stream-triad-omp-1M	0:00:46	2016-03-20 10:05:48	
CMNG317917	1025818	pjmucci	10	miniaero.exe	0:00:01	2016-03-20 10:09:22	
UQFM259478	1025819	pjmucci	1	stencil-27pt-50	0:00:03	2016-03-20 10:05:05	
OXBX917360	1025817	pjmucci	3	miniaero.exe	0:00:06	2016-03-20 10:04:42	
URGM160184	1025816	pjmucci	1	stream-copy-omp-1M	0:01:05	2016-03-20 10:05:41	
AYKC210492	1025815	pjmucci	1	miniaero.exe	0:00:04	2016-03-20 10:04:40	
NGOJ725228	1025814	pjmucci	1	stream-copy-omp-2G	0:02:39	2016-03-20 10:07:15	
WOPI548517	1025813	pjmucci	1	stream-triad-1M	0:00:46	2016-03-20 10:05:21	
FJGL475723	1025812	pjmucci	8	lulesh-opt	0:04:27	2016-03-20 10:09:03	

JOB DETAILS

RAW DATA | CLOCK SCALING | JOB OUTPUT | MODULES

Job Number: 1025844 Nodes Allocated: 16
Job Owner: pjmucci Nodes Used: 8

Job Script: miniaero-sbatch- MPI Ranks Used: 32 (map)

Job Path: ...tests/3D_Sod_Parallel_Big/miniaero.exe

Job Time: 0:26:23.075943 mpirun Time: 0:26:16.289926

Start Time: 2016-03-20 11:03:40 Finish Time: 2016-03-20 11:30:03

Job Info



JOB DETAILS

RAW DATA | CLOCK SCALING | JOB OUTPUT | MODULES

Job Number: 1025844 Job Owner: pjmucci

Job Script: miniaero-sbatch-

3d_sod_parallel_test_big.sh

Job Path: ...tests/3D_Sod_Parallel_Big/miniaero.exe

Job Time: 0:26:23.075943 mpirun Time: 0:26:16.289926 Start Time: 2016-03-20 11:03:40

Finish Time: 2016-03-20 11:30:03

N=\${N:-32} Nmo=\$((N - 1))

#slot | hwthread | core | socket (default) | numa | board | node
policy=\${policy:-"--map-by socket:PE=8"}

echo "Running parallel 3D sod test using \$policy and \$N processors." mpirun \$policy -np \$N .././make/src/miniaero.exe

diff=0

for i in 'seq 0 \$Nmo';

do

../tools/numeric_text_diff results.\$i results.\$i.gold > diff.\$i.txt

diff=\$((\$diff + \$?))

done

if [\$diff -at 0 1:

Nodes Allocated: 16
Nodes Used: 8

MPI Ranks Used: 32 (map)

Threads: 1

binutils/2.25.0 mpc/1.0.1 mpfr/3.1.2 gmp/6.0.0 isl/0.12.2 gcc/4.9.3 openmpi/1.10.0/gcc/4.9.3 python/2.7.9 mmperftools perfminer minimalmetrics

zlib/1.2.8 binutils/2.25.0 mpc/1.0.1 mpfr/3.1.2 gmp/6.0.0 isl/0.12.2 gcc/4.9.3

openmpi/1.10.0/gcc/4.9.3

python/2.7.9 mmperftools perfminer minimalmetrics

PerfMiner

Running parallel 3D sod test using --map-by socket:PE=8 and 32 processors. script: miniaero-sbatch-3d_sod_parallel_test_big.sh

mpiP: Found MPIP environment variable [-y -k 0 -e -p -q -f slurm-1025844.perfminer]

mpiP: Set the callsite stack traceback depth to [0]. mpiP: Set the output directory to [slurm-1025844.perfminer].

mpiP:

mpiP: mpiP: mpiP V3.4.2 (Build Feb 17 2016/04:46:45)

mpiP: Direct questions and errors to mpip-help@lists.sourceforge.net $\parbox{\cite{Minimation}}$

mpiP:

... Face creation time: 1.00 seconds ...

... Extract BC face and delete ghost time: 0.00 seconds ... Start setup communication.

... Setup Communcation function time: 0.00 seconds ...

... Rest of setup communication time: 1.00 seconds ... End setup communication.

... Setup time: 3.00 seconds ...

Job Info



JOB DETAILS

RAW DATA | CLOCK SCALING | JOB OUTPUT | MODULES

 Job Number:
 1025844
 Nodes Allocated:
 16

 Job Owner:
 pjmucci
 Nodes Used:
 8


 Job Script:
 miniaero-sbatch MPI Ranks Used:
 32 (map)

3d_sod_parallel_test_big.sh
Threads: 1

Job Path: ...tests/3D_Sod_Parallel_Big/miniaero.exe

Job Time: 0:26:23.075943
mpirun Time: 0:26:16.289926
Start Time: 2016-03-20 11:03:40
Finish Time: 2016-03-20 11:30:03

FREQUENCY SCALING




© Minimal Metrics LLC 2015


Metric Correlation



JOB DETAILS

JOB OVERVIEW






Metric Correlation



JOB PERFORMANCE DETAILS






Metric Correlation




JOB PERFORMANCE DETAILS





MPI







THE END!

<u>jeacook@sandia.gov</u> phil@minimalmetrics.com

MPI, Outlier Detection, Productivity 🗅



